



DESCRIPTION

The AM3407 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a load switch or in PWM applications.

The AM3407 is available in SOT-23 package.

FEATURES

- $V_{DS} = -30V, I_D = -4.1A$
 $R_{DS(ON)} < 95m\Omega @ V_{GS} = -4.5V$
 $R_{DS(ON)} < 65m\Omega @ V_{GS} = -10V$
- High Power and current handling capability
- Surface Mount Package
- Available in SOT-23 Package


ORDERING INFORMATION

Package Type	Part Number	
SOT-23	E3	AM3407E3R
		AM3407E3VR
Note	V: Halogen free Package R: Tape & Reel	
AiT provides all RoHS products		
Suffix “ V “ means Halogen free Package		

APPLICATION

- PWM applications
- Load switch
- Power management


P CHANNEL MOSFET



Schematic diagram



PIN DESCRIPTION



Top View

Pin #	Symbol	Function
1	G	Gate
2	S	Source
3	D	Drain



ABSOLUTE MAXIMUM RATINGS

T_A=25°C, unless otherwise noted

V _{DS} , Drain-Source Voltage	-30V
V _{GS} , Gate-Source Voltage	±20V
I _D , Drain Current-Continuous	-4.1A
I _{DM} , Drain Current-Pulsed ^{NOTE1}	-20A
P _D , Maximum Power Dissipation	1.4W
T _J , T _{STG} , Operating Junction and Storage Temperature Range	-55°C ~150°C

Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL CHARACTERISTICS

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Ambient ^{NOTE2}	R _{θJA}	90	°C/W



ELECTRICAL CHARACTERISTICS

T_A=25°C, unless otherwise noted

Parameter	Symbol	Conditions	Min	Typ.	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	B _{VDSS}	V _{GS} =0V, I _D =-250μA	-30	-33	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-24V, V _{GS} =0V	-	-	-1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
On Characteristics NOTE 3						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	-1	-1.5	-3	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =-10V, I _D =-4.1A	-	55	65	mΩ
		V _{GS} =-4.5V, I _D =-4A	-	75	95	
Forward Transconductance	g _{FS}	V _{DS} =-5V, I _D =-4.1A	5.5	-	-	S
Dynamic Characteristics NOTE 4						
Input Capacitance	C _{iss}	V _{DS} =-15V, V _{GS} =0V, F=1.0MHz	-	700	-	pF
Output Capacitance	C _{oss}		-	120	-	
Reverse Transfer Capacitance	C _{rss}		-	75	-	
Switching Characteristics NOTE 4						
Turn-on Delay Time	t _{d(on)}	V _{DD} =-15V, R _L =3.6Ω V _{GS} =-10V, R _{GEN} =3Ω	-	9	-	ns
Turn-on Rise Time	t _r		-	5	-	
Turn-Off Delay Time	t _{d(off)}		-	28	-	
Turn-Off Fall Time	t _f		-	13.5	-	
Total Gate Charge	Q _g	V _{DS} =-15V, I _D =-4A, V _{GS} =-10V	-	14	-	nC
Gate-Source Charge	Q _{gs}		-	3.1	-	
Gate-Drain Charge	Q _{gd}		-	3	-	
Drain-Source Diode Characteristics						
Diode Forward Voltage ^{NOTE3}	V _{SD}	V _{GS} =0V, I _S =-1A	-	-	-1.2	V

NOTE1: Repetitive Rating: Pulse width limited by maximum junction temperature.

NOTE2: Surface Mounted on FR4 Board, t ≤ 10 sec.


NOTE3: Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.

NOTE4: Guaranteed by design, not subject to production




TYPICAL PERFORMANCE CHARACTERISTICS


1. Power Dissipation




2. Drain Current




3. Output Characteristics




4. Drain-Source On-Resistance



5. Transfer Characteristics




6. Drain-Source On-Resistance







7. $R_{DS(on)}$ vs. V_{GS}




8. Capacitance vs. V_{DS}




9. Gate Charge



10. Source- Drain Diode Forward




11. Safe Operation Area






12. Normalized Maximum Transient Thermal Impedance




TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

1. Switching Test Circuit




2. Switching Waveforms





PACKAGE INFORMATION

Dimension in SOT-23 Package (Unit: mm)



SYMBOL	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.500	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.