



DESCRIPTION

The SM320A~SM3200A are available in SMA package.

ORDERING INFORMATION

Package Type	Part Number
SMA	SM320A
	SM340A
	SM360A
	SM380A
	SM3100A
	SM3120A
	SM3150A
	SM3200A
Note	SPQ: 5,000pcs/Reel
AiT provides all RoHS Compliant Products	

FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Available in SMA package

MECHANICAL DATA

Case: SMA

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 60mg / 0.0021oz

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbol	SM 320A	SM 340A	SM 360A	SM 380A	SM 3100A	SM 3120A	SM 3150A	SM 3200A	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS Voltage	V_{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	3.0								A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	80				70				A
Max Instantaneous Forward Voltage at 3A	V_F	0.55	0.70		0.85		0.95		V	
Maximum DC Reverse Current at Rated DC Reverse Voltage	I_R	$T_A=25^\circ\text{C}$ 0.5			$T_A=100^\circ\text{C}$ 0.3				mA	
		5			3					
Typical Junction Capacitance ^{NOTE1}	C_J	450			400				pF	
Typical thermal Resistance ^{NOTE2}	$R_{\theta JA}$	70								°C/W
Operating Junction Temperature Range	T_J	-55 to +125								°C
Storage Temperature Range	T_{stg}	-55 to +150								°C

NOTE1: Measured at 1MHz and applied reverse voltage of 4 V D.C.

NOTE2: P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



TYPICAL PERFORMANCE CHARACTERISTICS

Figure. 1 Forward Current Derating Curve




Figure. 2 Typical Reverse Characteristics




Figure. 3 Typical Forward Characteristic




Figure. 4 Typical Junction Capacitance




Figure. 5 Maximum Non-Repetitive Peak Forward Surge Current






Figure. 6 Typical Transient Thermal Impedance






PACKAGE INFORMATION

Dimension in SMA Package (Unit: mm)



The recommended mounting pad size



Unit : $\frac{\text{mm}}{\text{(mil)}}$

UNIT		A	D	E	H _E	c	e	g
mm	max	2.2	4.83	2.9	5.4	0.31	1.7	1.5
	min	1.9	4.32	2.3	4.7	0.12	1.2	0.9
mil	max	87	190	114	213	12	67	59
	min	75	170	91	185	5	47	35



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or server property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.